

DOT-DASH[®] SIGNAGE / INSTALLATION PANEL MOUNT (TOP & SIDE)-Q SYSTEM

TOP PANEL: With the top cap removed, the bracket is fastened to the side of the top cap just under the top cap "lip" with the adhesive provided on the back of the bracket. Remove the release liner exposing the adhesive and press bracket firmly onto the top cap.

OPTIONAL: a #6 x 1/2" screw is provided to either attach the bracket to the existing 1/8" holes at either end (both sides) of the top cap or otherwise a 1/8" hole must be drilled for an alternate sign location along the top of the panel. Use the hole in the bracket as a template for drilling.



SIDE PANEL: Bracket clips into the slots of the hanger frame. A #6 x 1/2" pan head screw (provided) secures the bracket to the panel and prevents the bracket from "hinging". Do not drill a hole. Use a screw driver and the hole in the bracket as a template to align and fasten the screw through the fabric into the fiber board at the side of the panel.



The back half of the dot is attached to the bracket with a #8-32 x 5/8" flat head screw. A 3/32" allen wrench (provided) is required to loosen or tighten the screw. The dot can rotate with this screw loose to position the plaque.

The screw holding the back half of the dot to the bracket **must be firmly tightened** to hold the dot and the plaque in desired position.

Hold plaque against shoulder of dot and turn cap and washer tightly against plaque, (rubber side of washer against plaque).

